



Form A - EN 175301-803 (DIN43650) / ISO 4400

Product description		EN175301-803	EN175301-803
Standard		EN175301-803	EN175301-803
Construction type		A	A
Description		P18 connector with screw terminals NBR profile gasket (PE) earth position H12	P18 connector with screw terminals NBR profile gasket (PE) earth position H12
Housing colour		black	black
Number of contacts		2+PE	2+PE
Order no.		KA132000B9	KA132000B1
Other options on request	grey housing	order no. KA132000A9	order no. KA132000A1
Cable gland		PG9	PG11
Max. conductor size		1,5mm ² without splice/terminal	1,5mm ² without splice/terminal
Drawing			
Technical data			
Pin dimension		6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
Rated voltage max.		250 V AC/DC	250 V AC/DC
Rated current max. (EN 60512-5-2 test 5b)		10 A	10 A
Contact resistance		15mΩ max.	15mΩ max.
Overvoltage category		III	III
Type of termination		screw M3	screw M3
Contact screw torque		max. 0,5 N/m	max. 0,5 N/m
Suitable cables		5 mm to 7 mm diameter	6 mm to 9 mm diameter
Mounting		central screw M3x32,5	central screw M3x32,5
Material			
Contact holder material		PA6 GF	PA6 GF
Housing material		PA6 GF	PA6 GF
Environmental conditions			
Protection class (EN 60529)		IP 65 when correctly assembled	IP 65 when correctly assembled
Pollution severity (EN 60664-1)		3	3
Temperature range		-40°C to + 100°C	-40°C to + 100°C
	with silicon gasket	-40°C to + 125°C	-40°C to + 125°C
Inflammability class			
Contact holder		HB - UL 94	HB - UL 94
Housing		HB - UL 94	HB - UL 94
Approvals		VDE	VDE
Packaging			
Packaging unit / Weight approx.		500 pieces / 14,5Kg	500 pieces / 14,5Kg
Box dimensions		80 x 30 x 22 cm	80 x 30 x 22 cm
Other accessory options			
to be ordered separately see pages 171-175		NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag